



# SAFETY DATA SHEET

Revision Date: 19/May/2015

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product Identifier**

**Product Description:** **KBP HFST Binder Resin**

**Other means of identification**

**Material Codes:** KBP HFST Binder Resin, PolyLite® 32042-11  
**Chemical Family** Polyester Resin

**Recommended use of the chemical and restrictions on use**

**Intended Use:** Concrete Resin  
**Uses advised against** No information available

**Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**  
Kwik Bond Polymers, LLC.  
923 Teal Drive  
Benicia, CA 94510  
(866) 434-1772

**Emergency Telephone** (800) 373-7542

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Sub-category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Chronic aquatic toxicity	Category 3
Flammable liquids	Category 3


**Label elements**

**Emergency Overview**

**Danger**

**Hazard Statements**

Harmful in contact with skin  
Harmful if inhaled  
Causes severe skin burns and eye damage  
May cause cancer  
May cause respiratory irritation  
Causes damage to hearing through prolonged or repeated exposure if inhaled  
Harmful to aquatic life with long lasting effects  
Flammable liquid and vapor



**Appearance** Purple

**Physical State** Liquid

**Odor** Pungent

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Use only outdoors or in a well-ventilated area
- Do not breathe mist/vapors/spray
- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not eat, drink or smoke when using this product
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Precautionary Statements - Response**

- IF IN EYES, ON SKIN, IF INHALED, IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- Wash contaminated clothing before reuse
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- If skin irritation occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- In case of fire: Use CO2, dry chemical, or foam to extinguish

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to industrial incineration plant  
 Dispose of in accordance with federal, state and local regulations

**Hazards not otherwise classified (HNOC)**

Other Information

Unknown acute toxicity                      70.6 % of the mixture consists of ingredient(s) of unknown toxicity  
 Unknown aquatic toxicity                      81.6 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight-%	Trade Secret
Polyester Resin	Proprietary	70.6	
Styrene	100-42-5	18	
Diluent	Proprietary	9 - 11	*

Cobalt compounds	Proprietary	< 0.15	*
------------------	-------------	--------	---

\* The exact percentage (concentration) of composition has been withheld as a trade secret. If CAS number is "proprietary", the specific chemical identity has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### First Aid Measures

<b>Eye Contact</b>	Immediately flush eyes for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water. Remove contaminated clothing and shoes. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Remove person to fresh air. If signs/symptoms continue, get medical attention. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is labored, administer oxygen. Get medical attention immediately.
<b>Ingestion</b>	Do NOT induce vomiting. CORROSIVE. Potential for aspiration if swallowed. This material may enter the lungs during vomiting. Never give anything by mouth to an unconscious person. GET IMMEDIATE MEDICAL ATTENTION.

##### Most important symptoms and effects, both acute and delayed

<b>Most Important Symptoms and Effects</b>	The product causes burns of eyes, skin and mucous membranes. Harmful by inhalation, in contact with skin and if swallowed.
--	--

##### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>), Foam, Dry chemical, Water spray

##### Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

<b>Hazardous combustion products</b>	Combustion may produce carbon monoxide, carbon dioxide and irritating or toxic vapors and gases
<b>Combustion/Explosion Hazards</b>	Flammable. Vapors may form explosive mixture with air. Flash back possible over considerable distance. This material may polymerize (react) when its container is exposed to heat (as during a fire). This polymerization increases pressure inside a closed container and may result in the violent rupture of the container. Empty containers may retain product residue (liquid and/or vapor). Do not pressurize, cut, weld, braze, solder, drill, grind, or expose these containers to heat, flame, sparks, static electricity, or other sources of ignition as the container may explode and may cause injury or death.

##### Protective Equipment and Precautions for Firefighters:

Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazard while extinguishing the blaze. DO NOT extinguish a fire resulting from the flow of this flammable liquid until the flow of liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished. Use water spray to cool fire-exposed containers.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

**Environmental Precautions**

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

**Methods and material for containment and cleaning up**

**Methods for Containment** Prevent spilled material from 1) contaminating soil, 2) entering sanitary sewers, storm sewers, and drainage systems, and 3) entering bodies of water or ditches that lead to waterways. Prevent spreading over a wide area (e.g. by containment or oil barriers).

**Methods for Clean-up** Soak up with inert absorbent material. Remove from surface water (e.g. by skimming or siphoning). Dispose of contaminated material as waste according to item 13.

**7. HANDLING AND STORAGE****Precautions for Safe Handling**

**Handling** Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse. Ensure adequate ventilation. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. Consult your supplier of promoters and catalysts for additional instructions on proper mixing and usage. Empty containers may retain product residue (liquid and/or vapor). Do not pressurize, cut, weld, braze, solder, drill, grind, or expose these containers to heat, flame, sparks, static electricity, or other sources of ignition as the container may explode and may cause injury or death. Empty drums should be completely drained and properly bunged. Empty drums should be promptly returned to a drum reconditioner or properly disposed.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from heat and sources of ignition. No smoking. Keep away from direct sunlight. Keep containers tightly closed in a cool, well-ventilated place. To ensure maximum stability and maintain optimum resin properties, resins should be stored in closed containers at temperatures below 77°F (25°C).

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure limits**

Components with workplace control parameters

**Styrene (CAS #: 100-42-5)**

ACGIH TLV

20 ppm TWA  
40 ppm STEL  
A4 Not Classifiable as a Human Carcinogen  
100 ppm TWA  
200 ppm Ceiling

OSHA PEL

Industry PEL

While the federal workplace exposure limit for styrene is 100 ppm, OSHA accepted the styrene industry's proposal to voluntarily meet a PEL of 50 ppm on an 8 hour TWA and a Short Term Exposure Limit (STEL) of 100 ppm, 15 minute exposure.

Canada - Alberta OELs	40 ppm STEL 170 mg/m <sup>3</sup> STEL 20 ppm TWA 85 mg/m <sup>3</sup> TWA
Canada - Ontario OELs	35 ppm TWA 100 ppm STEL
Canada - British Columbia OELs	50 ppm TWA 75 ppm STEL
NIOSH IDLH	700 ppm Immediately dangerous to life or health IDLH
Mexico OEL	100 ppm STEL 425 mg/m <sup>3</sup> STEL 50 ppm TWA 215 mg/m <sup>3</sup> TWA (skin)
<b>Diluent (CAS #: )</b>	
ACGIH TLV	20 ppm TWA
Canada - Alberta OELs	20 ppm TWA 70 mg/m <sup>3</sup> TWA
Canada - Ontario OELs	20 ppm TWA
Canada - British Columbia OELs	20 ppm TWA

**Legend**ACGIH (*American Conference of Governmental Industrial Hygienists*)TLV® (*Threshold Limit Value*)TWA (*time-weighted average*)STEL - *Short Term Exposure Limit*OSHA - *Occupational Safety and Health Administration*PEL - *Permissible Exposure Limit*OEL - *Occupational Exposure Limit*NIOSH - *National Institute for Occupational Safety and Health*IDLH - *Immediately Dangerous to Life or Health*SKIN: *Skin Absorption***Appropriate engineering controls****Engineering Controls**

Use general ventilation to maintain airborne concentrations to levels that are below regulatory and recommended occupational exposure limits. Local ventilation may be required during certain operations. Use explosion-proof equipment.

**Individual protection measures, such as personal protective equipment****Eye/face Protection**

Wear safety glasses with side shields and a faceshield or goggles and a faceshield. Ensure that eyewash stations and safety showers are close to the workstation location.

**Skin Protection**

Wear protective nitrile rubber or Viton™ gloves. Gloves made of nitrile rubber or polyvinyl chloride (PVC) may be used for splash protection and brief or intermittent contact with styrenated polyester resin. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Impervious clothing. Rubber or plastic boots.

**Respiratory Protection**

None required if hazards have been assessed and airborne concentrations are maintained below the exposure limits listed in Section 8. Wear an approved air-purifying respirator with organic vapor cartridges and particulate filters where airborne concentrations may exceed exposure limits in Section 8 and/or there is exposure to dust or mists due to sanding, grinding, cutting, or spraying. Use an approved positive-pressure air-supplied respirator with emergency escape provisions if there is any potential for an uncontrolled release, airborne concentrations are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Purple
Odor	Pungent
Odor Threshold	0.2 ppm (Styrene)
Physical State	Liquid
pH	No information available
Flash Point	32 °C / 89 °F
Flash Point Method:	Seta closed cup
Autoignition Temperature	490°C / 914°F (Styrene)
Boiling point / boiling range	146°C / 295°F (Styrene)
Melting point / Freezing point	No information available
Flammability Limit in Air	
Lower	1.1% (Styrene)
Upper	6.1% (Styrene)
Specific Gravity	1.11 - 1.19 @ 25°C
Solubility	Insoluble (Water)
Evaporation Rate	0.49 (BuAc = 1) (Styrene)
Vapor Pressure	5 mmHg @ 20°C (Styrene)
	6.7 hPa (Styrene)
Vapor Density	3.6 (Air = 1) (Styrene)
Explosive Properties	No information available
Oxidizing Properties	No information available
Percent Volatile, wt.%	41 - 44 % by weight
VOC Content:	322 g/l (calculated) product as supplied
Viscosity	1000 - 1200 cps @ 25°C
Partition Coefficient (n-octanol/water)	No information available
Decomposition temperature	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No dangerous reaction known under conditions of normal use.

### Chemical Stability

Stable under normal conditions. Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

#### **Hazardous Polymerization**

Polymerization can occur. Hazardous polymerization will occur if contaminated with peroxides, metal salts and polymerization catalysts. Product will undergo hazardous polymerization at temperatures above 150 F (65 C).

#### **Conditions to Avoid**

Heat, flames and sparks. Contamination by those materials referred to under Incompatible materials.

#### **Incompatible materials**

Strong acids. Strong oxidizing agents. Metal salts. Polymerization catalysts.

#### **Hazardous Decomposition Products**

Hydrocarbons. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Primary Routes of Entry**

Eye contact, Ingestion, Inhalation, Skin Contact, Skin absorption

#### **Acute toxicity**

##### **Styrene**

Oral LD50	= 5000 mg/kg (Rat)
Dermal LD50	> 2000 mg/kg (Rat)
Inhalation LC50	= 11.8 mg/l (4 H) (Rat)

<b>Diluent</b>	
Oral LD50	= 1060 mg/kg (Rat)
Dermal LD50	= 500 mg/kg (Rabbit)
Inhalation LC50	7.1 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Eyes** Causes severe eye irritation. May cause burns. May cause irreversible eye damage.

**Skin** Harmful by skin absorption. Contact causes severe skin irritation and possible burns.

**Inhalation** Harmful by inhalation. May cause delayed lung injury and burns. Inhalation of high vapor concentrations can cause CNS-depression and narcosis.

**Ingestion** Harmful if swallowed. Ingestion causes burns of the upper digestive and respiratory tracts. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. Ingestion is not an anticipated route of exposure for this material in industrial use.

**Sensitization** No information available.

**Repeated dose toxicity** In humans, styrene may cause a transient decrease in color discrimination and effects on hearing. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to defatting properties of the product. May cause damage to the kidneys, liver, eyes, brain, respiratory system, central nervous system through prolonged or repeated exposure if inhaled.

**Mutagenic effects** Styrene has given mixed positive and negative results in a number of mutagenicity tests. Styrene was not mutagenic without metabolic activation but gave negative and positive mutagenic results with metabolic activation.

**Carcinogenicity****Styrene**

**ACGIH**  
**IARC**  
**NTP**

Group A4 - Not classifiable as a human carcinogen.  
Group 2B - Possibly Carcinogenic to Humans  
Reasonably anticipated to be human carcinogen

**Cobalt compounds**

**IARC**

Group 2B - Possibly Carcinogenic to Humans

**Legend**

*IARC - International Agency for Research on Cancer*  
*NTP - National Toxicology Program*

**Reproductive Toxicity** No information available.

**Neurological Effects** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Target organ(s)** Liver, Kidney, Central nervous system (CNS), Respiratory system, Eyes, Skin.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** 70.6 % of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	2250 mg/kg
ATEmix (dermal)	1626 mg/kg
ATEmix (inhalation-dust/mist)	5936 mg/L
ATEmix (inhalation-vapor)	19.3 mg/L

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### **Styrene**

Log Kow	2.95
Bioconcentration factor (BCF)	74
Algae	EC50 = 1.4 mg/L (Pseudokirchneriella subcapitata) (72h) EC50 0.46 - 4.3 mg/L (Pseudokirchneriella subcapitata) (72h)
Fish	LC50 3.24 - 4.99 mg/L (Pimephales promelas) (96 h) flow-through LC50 19.03 - 33.53 mg/L (Lepomis macrochirus) (96 h) static LC50 6.75 - 14.5 mg/L (Pimephales promelas) (96 h) static LC50 58.75 - 95.32 mg/L (Poecilia reticulata) (96 h) static EC50 3.3 - 7.4 mg/L 48 h
Water Flea	

#### **Diluent**

Log Kow	0.93
---------	------

#### **Cobalt compounds**

Algae	EC50 = 0.639 mg/L
-------	-------------------

#### **Unknown aquatic toxicity**

81.6 % of the mixture consists of components(s) of unknown hazards to the aquatic environment.

#### **Persistence/Degradability**

No information available.

#### **Bioaccumulation**

No information available.

#### **Other adverse effects**

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Considerations**

Hazardous waste. Can be incinerated, when in compliance with local regulations.

#### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

#### **US EPA Waste Number**

D001 (IGNITABLE): When discarded in its purchased form, this material would be regulated under 40 CFR 261.21 as EPA Hazardous Waste Number D001 based on the characteristic of ignitability.

## 14. TRANSPORT INFORMATION

### DOT

UN-No	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	III
NAERG:	127

### TDG



<b>UN-No</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	CLASS 3
<b>Packing Group</b>	PG III
<b>NAERG:</b>	127

**MEX**

<b>UN-No</b>	UN2920
<b>Proper Shipping Name</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
<b>Technical Name:</b>	METHACRYLIC ACID
	STYRENE
<b>Hazard Class</b>	CLASS 8
<b>Subsidiary Class</b>	3
<b>Packing Group</b>	PG II
<b>NAERG:</b>	132

**IATA**

<b>UN-No</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Packing Instructions</b>	355, 366
<b>NAERG:</b>	127

**IMDG/IMO**

<b>UN-No</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	CLASS 3
<b>Packing Group</b>	PG III
<b>EmS-No</b>	F-E, S-E
<b>NAERG:</b>	127

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA Inventory Status:</b>	All components of this material are listed on or are exempt from the US Toxic Substances Control Act (TSCA) inventory.
<b>Canadian Inventory Status:</b>	This material contains components that are NOT listed on the Canadian Domestic Substances List (DSL)
<b>Australian Inventory Status:</b>	This product contains one or more chemicals currently not on the Australian Inventory of Chemical Substances
<b>Korean Inventory Status:</b>	This product contains one or more chemicals currently not on the Korean Chemical Substances List
<b>Philippine Inventory:</b>	All components of this material are listed on or are exempt from the Philippine Inventory of Chemicals and Chemical Substances
<b>Japan ENCS:</b>	This product contains one or more chemicals currently not on the Japanese Inventory of Existing and New Chemical Substances
<b>Chinese IECS:</b>	This product contains one or more chemicals currently not on the Chinese Inventory of Existing Chemical Substances
<b>New Zealand Inventory:</b>	All components of this material are listed on or are exempt from the New Zealand Inventory of Chemicals

**US Federal Regulations****TSCA 12(b) - Export Notification:**

This material does not contain any components that are subject to the US Toxic Substances Control Act (TSCA) Section 12(b) Export Notification requirements.

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Component	CAS No	Weight-%	SARA 313 Status
Styrene	100-42-5	18	Listed
Cobalt compounds		< 0.15	Listed

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	Yes

**Clean Water Act**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb			Listed

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Component	CAS No	Weight-%	HAPS data
Styrene	100-42-5	18	
Cobalt compounds		< 0.15	Listed

**CERCLA**

This product contains the following reportable quantities:

Component	40 CFR 302.4 RQ	40 CFR 355 EHS TPQs
Styrene	1000 lb 454 kg	

**Chemical Weapons Convention (CWC)**

This product does not contain any listed substances.

**State Regulations****California Proposition 65**

WARNING: This material contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. The California Safe Drinking Water and Toxic Enforcement Act of 1986 requires that clear and reasonable warning be given prior to exposing any person to this chemical.

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

<b>16. OTHER INFORMATION</b>
------------------------------

**NFPA Rating**

Health 3

Flammability 3

Instability 1

**Prepared By**

Kwik Bond Polymers, LLC Product  
Regulatory Department Phone Number:  
(866) 434-1772

**Revision Date:**

19/May/2015

**Revision Summary:** This data sheet contains changes from the previous version in section(s):  
2, 3, 4, 5, 11, 14, 15

**Former date:** 31 July 2014

This information is provided in good faith and is correct to the best of Kwik Bond's knowledge as of the date hereof and is designed to assist our customers; however, Kwik Bond makes no representation as to its completeness or accuracy. Our products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use and to satisfy themselves as to suitability for their specific applications. Any use which Kwik Bond's customers or third parties make of this information, or any reliance on, or decisions made based upon it, are the responsibility of such customer or third party. Kwik Bond disclaims responsibility for damages, or liability, of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES. IN NO EVENT SHALL KWIK BOND BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**